






60D20

3~ 50 Hz. 400V	
DEUTZ	
EU STAGE 2	
69 db(A) @ 7 mt	
120 lt	

AGG. 11/20

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
60	48	66	52,8

ENVIRONMENTAL CONDITIONS	
Temperature	40° C
Height	1000 mslm
Humidity	60%

OPEN VERSION B50
SOUNDPROOF VERSION C100


The image is only for demonstration purposes

The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
820	1650	850	1650

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
1290	2300	1050	1590

TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	86,6	A
ENGINE	Engine	DEUTZ BF4M 2011 C	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 2	
	RPM governor	Mechanical	
	Performance class (ISO8528-5)	G2	
	Rpm	1500	rpm
	Nr. of cylinders	4	
	Bore x stroke	94 x 112	mm
	Displacement	3108	cc
	Induction system	Turbocharged	
	Cooling system	Oil	
	Engine net prime power	75,2 (56,1)	Hp (kW)
Exhaust gas aftertreatment	/		
CONSUMPTION	Fuel type	Diesel	
	Consumption @ 50-75-100% load	7-10,5,14,2	lt/h
	Standard tank capacity	120	lt
	Autonomy @ 75% load	11,4	h
ALTERNATOR	Alternator	STAMFORD – MECC ALTE – MARELLI MOTORI	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
GENERAL	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	90	mm
	Electrical system voltage	12	V

ELECTRIC PANEL

MANUAL



AUTOMATIC MAINS FAILURE



Electronic control unit with multimeter	LOVATO ELECTRIC RGK420SA	COMAP IntelliLite 9
Electrical panel enclosure protection degree	IP44	
ON-OFF electric panel switch	Key type. In-built the control unit	Without key
Emergency pushbutton	STANDARD	
Battery charge maintainer	/	12V 5A
Power supply	Full power terminal	Full power terminal
Circuit breaker	Magnetothermal type 4P ABB Tmax-XT 80A	Magnetothermal type 4P ABB Tmax-XT 80A
Main protection alarms	Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level	

STANDARD ELECTRONIC CONTROL UNIT

LOVATO ELECTRIC
RGK420 SA



Functions: manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1), Hz, kVA, battery V, hour counter

Backlit LCD display. Optical port and NFC

COMAP
IntelliLite 9



Functions: automatic or manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter

Backlit LCD display. USB port

Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS

OPTIONAL ELECTRONIC CONTROL UNIT




DEEP SEA DSE4520 MKII
DEEP SEA DSE7320 MKII





COMAP AMF25

SOUNDPROOF AND WEATHERPROOF CANOPY



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 2,5 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 1,5 and 4,5 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL 5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	120 lt+ Drip tray
<i>Soundproofing coating material</i>	<i>Polyester fiber. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>In-built the canopy. Residential type with sound reduction 35 dB(A)</i>
<i>Access openings</i>	<i>n.3 doors with key lock</i>
<i>Electric panel</i>	<i>Lateral side position. Dedicated door with padlockable key lock</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.2 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

CONTAINER TRANSPORTABILITY ADVANTAGES

VERSION	20' BOX	40' BOX	40' HC
 <i>N. transportable pieces</i>	5	10	10
	5	10	10

MAIN OPTIONS



90A automatic transfer switch (ATS)



250 lt bigger fuel tank with drip tray



350W engine preheating system



Electronic engine speed governor



Automatic fuel transfer kit with manual by-pass system



Residual current circuit breaker



Electric fuel floater to check the fuel level from the electronic control unit



Engine oil pressure and cooling water temperature measuring instruments

OTHER OPTIONS

Power distribution socket set
Synchronizing electric panel
Battery switch
Remote control systems **ETHERNET, 2G - 3G - 4G, GPS**

Further alternator brand
Quick couplings for connecting an external tank with three way valve
Outdoor, underground and transportable tanks -
Slow or fast towing trailer
Front hot air expulsion canopy
Further colors

VERSIONS WITH SPECIAL EQUIPMENT



RENTAL

Special version with features designed for the rental market



ZERO NOISE

Super sound-proofed special version, noise level 50, 55 or 60 dB(A)

Greenpower AB
Helsingborgsvägen Varalöv,
262 96 Ängelholm, Sweden
Phone: +46 43122240
Email: info@greenpower.se
Web: www.greenpower.se