

## TECHNICAL DATA SHEET

# GP115 TR/S

### STRUCTURE



*Gear Box/alternator monoblock unit coupled through shaft, installed on a welded, powder-painted carbon steel base frame with demountable legs. (images are for illustrative purpose only)*

#### ELECTRIC PANEL

Magnetothermic circuit breaker
Earth fault device
Power terminal board
Schuko sockets 16A 230V
E31 digital module:
- Voltmeter
- Frequency meter
- Hour counter

### TECHNICAL DATA

EQUIPMENT SPECIFICATION (ISO 8528/1)	50Hz
Prime power at cosfi 0.8	100 kVA
Prime power at cosfi 0.8	80 kW
Voltage available to the terminals	400/230 V
Dimensions (mm)	1140x750x1210
Weight (Kg)	572

GEAR BOX	50Hz
Brand and model	6084.338.035
R.P.M.	1500

ALTERNATOR	50Hz
Brand and model	MECC ALTE ECP34-2S/4 (*)
Synchronous with electronic governor voltage	± 1%
Pole	4
Stator/rotator insulation	H
Protection level	IP23
Continuous power	100 kVA

(\*) = or similar brand



**Greenpower AB**

Helsingborgsvägen Varalöv

262 96 Ängelholm

Tel: 0431 222 40

E-mail: info@greenpower.se

web: www.greenpower.se